



Light Source

2835 SMD

MacAdam Ellipse

3-Step

Substrate

Copper 3Oz

Input Voltage

DC 24V

Solder Pad

Immersion gold

Operating Temperature

-20°C~+45°C

Color Temperature

Dim-to-Warm 1800-3000K, others on request

Degree of Protection

IP00

CRI

95 90 80


Package

10m/reel

Lunga D2W (Dim-to-Warm) flexible strip is of linear dimming curve, available in 10, 15, 20, and 25 watts. The CCTs goes all the way down while they are being dimmed. Compatible with DALI, 0-10V, and triac control.

D2W strip replicates the glow and dimming of incandescent lamps by dynamically changing CCT from 3000K(others on request) to 1800K(others on request). The dim to warm effect provides a relaxing environment.

Linear Dimming Curve(15W)



Article No.	Type	LEDs	LEDs/m	Volt(DC)	Power(W)	Angle(°)	CCT(K)	CRI	Flux(lm)	Max Length(m)
Sh242518309012	CC	2835	140	24V	25.0	120	3000	90	2240	5
	CC	2835	140	24V	2.4	120	1800	90	130	5
Sh242018309012	CC	2835	140	24V	20.0	120	3000	90	1830	5
	CC	2835	140	24V	2.0	120	1800	90	110	5
Sh241518309012	CC	2835	140	24V	15.0	120	3000	90	1490	10
	CC	2835	140	24V	1.5	120	1800	90	80	10
Sh241018309012	CC	2835	140	24V	10.0	120	3000	90	990	10
	CC	2835	140	24V	1.0	120	1800	90	60	10

