



Light Source

5050 SMD

MacAdam Ellipse (White)

3-Step

Substrate

Copper 3Oz

Input Voltage

DC 24V

Solder Pad

Immersion gold

Operating Temperature

-20°C~+45°C

Color Temperature (White)

2700K 3000K 4000K 5700K

Degree of Protection

IP00

CRI (White)

90 80

Package

10m/reel

Article No.	Type	LEDs	LEDs/m	Color	Volt(DC)	Power(W)	Angle(°)	Wavelength/CCT	CRI	Flux(lm)	Max Length(m)
Sc2418RGBW308012	CC	Refond	48	R	24V	3.5	120	620-630nm	-	94	5
Sc2418RGBW308012	CC	Refond	48	G	24V	3.5	120	520-535nm	-	190	5
Sc2418RGBW308012	CC	Refond	48	B	24V	3.5	120	460-475nm	-	35	5
Sc2418RGBW308012	CC	Refond	48	W	24V	7.2	120	3000K	80	600	5
Sc2418RGBW309012	CC	Refond	48	W	24V	7.2	120	3000K	90	550	5
Sc2418RGBW308012	CC	Refond	96	RGBW	24V	18	120	4100K	80	900	5
Sc2418RGBW309012	CC	Refond	96	RGBW	24V	18	120	4100K	90	800	5
S2418RGBW308012	CV	Refond	48	R	24V	3.5	120	620-630nm	-	94	5
S2418RGBW308012	CV	Refond	48	G	24V	3.5	120	520-535nm	-	190	5
S2418RGBW308012	CV	Refond	48	B	24V	3.5	120	460-475nm	-	35	5
S2418RGBW308012	CV	Refond	48	W	24V	7.2	120	3000K	80	600	5
S2418RGBW309012	CV	Refond	48	W	24V	7.2	120	3000K	90	550	5
S2418RGBW308012	CV	Refond	96	RGBW	24V	18	120	4100K	80	900	5
S2418RGBW309012	CV	Refond	96	RGBW	24V	18	120	4100K	90	800	5

