



Light Source

2835 SMD

MacAdam Ellipse

3-Step

Substrate

Copper 3Oz

Input Voltage

DC 24V

Solder Pad

Immersion gold

Operating Temperature

-20°C~+45°C

Color Temperature

Tunable White 2700K - 5700K

Degree of Protection

IP00

CRI

95 90 80

Package

10m/reel

Article No.	Type	LEDs	LEDs/m	Volt(DC)	Power(W)	Angle(°)	CCT(K)	CRI	Flux(lm)	Max Length(m)
Sc240827578012	CC	Osram	216	24V	8	120	2700	80	770	10
Sc240827578012	CC	Osram	216	24V	8	120	5700	80	790	10
Sc241227578012	CC	Osram	216	24V	12	120	2700	80	1130	10
Sc241227578012	CC	Osram	216	24V	12	120	5700	80	1150	10
Sc241627578012	CC	Osram	216	24V	16	120	2700	80	1410	5
Sc241627578012	CC	Osram	216	24V	16	120	5700	80	1430	5
Sc242027578012	CC	Osram	216	24V	20	120	2700	80	1690	5
Sc242027578012	CC	Osram	216	24V	20	120	5700	80	1750	5
S240827578012	CV	Osram	216	24V	8	120	2700	80	770	5
S240827578012	CV	Osram	216	24V	8	120	5700	80	790	5
S241227578012	CV	Osram	216	24V	12	120	2700	80	1130	5
S241227578012	CV	Osram	216	24V	12	120	5700	80	1150	5
S241627578012	CV	Osram	216	24V	16	120	2700	80	1410	5
S241627578012	CV	Osram	216	24V	16	120	5700	80	1430	5
S242027578012	CV	Osram	216	24V	20	120	2700	80	1690	5
S242027578012	CV	Osram	216	24V	20	120	5700	80	1750	5

