



Light Source

2835 SMD

MacAdam Ellipse

3-Step

Substrate

Rolled copper 4Oz

Input Voltage

DC 24V

Solder Pad

Immersion gold

Operating Temperature

-20°C~+45°C

Color Temperature

2700K 3000K 4000K 5700K

Degree of Protection

IP00

CRI

95 90

Package

10m/reel

LUNGA premium is a series of LED strips equipped with current regulators and 7pcs San'an chipsets 95Ra on every smallest segment.

We upgrade the thickness of the copper foil to 4 ounces, resulting in an increase of maximum length from 5 to 8 meters.

There are 4 wattages(25W, 20W, 15W, 10W) to choose from in one strip by adjusting the current regulator.

Light output is not affected by voltage drop within a certain length.

Suitable for application where budget is adequate and a long run is necessary.

Article No.	LEDs	LEDs/m	Volt(DC)	Power(W)	Angle(°)	CCT(K)	CRI	Flux(lm)	Efficacy(lm/w)	Max Length(m)
Sc2425309510	San'an	154	24V	25	120	3000	95	2160	86	8
Sc2420309510	San'an	154	24V	20	120	3000	95	1810	90	10
Sc2415309510	San'an	154	24V	15	120	3000	95	1430	95	13
Sc2410309510	San'an	154	24V	10	120	3000	95	1000	100	15
Sc2420309010H	Bridgelux	154	24V	20.2	120	3000	90	2810	139	10
Sc2416309010H	Bridgelux	154	24V	15.8	120	3000	90	2180	138	13
Sc2410309010H	Bridgelux	154	24V	10	120	3000	90	1380	138	15
Sc2406309010H	Bridgelux	154	24V	6	120	3000	90	840	140	18

