



Input Voltage

AC 220-240V

Installation

Suspended

Control

Integrated DALI power supply

Degree of Protection

IP20

Color Temperature




2700K 3000K 3500K 4000K 5000K 5700K

Finish

Matt white Matt black Custom powder coating

Diffuser

Opal Micropismatic



Article No.	AC Input(V)	Control	DALI Addresses	P(W)	Angle(°)	CCT(K)	CRI	Flux(lm)	Efficacy(lm/W)	Dims(mm)	Segments
RL1000DD0653090	220-240	DALI	1	65	90	3000	90	7150	110	Ø1000*H75*W60	1
RL1500DD0993090	220-240	DALI	2	99	90	3000	90	10890	110	Ø1500*H75*W60	1
RL1800DD1203090	220-240	DALI	2	120	90	3000	90	13200	110	Ø1800*H75*W60	2
RL3000DD2003090	220-240	DALI	4	200	90	3000	90	22000	110	Ø3000*H75*W60	4
RL1000DI0650213090	220-240	DALI	1	65 / 21	90	3000	90	7150 / 1680	110 / 80	Ø1000*H75*W60	1
RL1500DI0990323090	220-240	DALI	2	99 / 32	90	3000	90	10890 / 2560	110 / 80	Ø1500*H75*W60	1
RL1800DI1200403090	220-240	DALI	3	120 / 40	90	3000	90	13200 / 3200	110 / 80	Ø1800*H75*W60	2
RL3000DI2000653090	220-240	DALI	5	200 / 65	90	3000	90	22000 / 5200	110 / 80	Ø3000*H75*W60	4

Custom width 40-200mm / Custom diameter 400mm - 6000mm / Custom lines, shapes, and patterns.

