



Light Source

Bridgelux

MacAdam Ellipse

2-Step 3-Step

Material

Turning aluminum + PC lens

Degree of Protection

IP40

Color Temperature

2700K 3000K 4000K D2W

CRI

97 90 80

Tilt Angle


25°



Module



Article No.	LED	P(W)	CC(mA)	Voltage(V)	Angle(°)	CCT(K)	CRI	Flux(lm)
MP-6-30-30-90	V8	6.1	350	17.4	30	3000	90	570
MP-6-40-30-90	V8	6.1	350	17.4	40	3000	90	570
MP-9-30-30-90	Vero 10	8.9	350	25.3	30	3000	90	860
MP-9-40-30-90	Vero 10	8.9	350	25.3	40	3000	90	870
MPL-6-24-1830-90	Vesta	0.2-6	14-350	11.2-17	24	Dim to Warm 1800-3000	90	12-510
MPL-6-36-1830-90	Vesta	0.2-6	14-350	11.2-17	36	Dim to Warm 1800-3000	90	12-510



Anti-glare Part

Article No.	Finish	Installed LED Module	Angle(°)	Flux(lm)	UGR
FP-AG-MB	Matt Black	MP-6-30-30-90	30	510	9
		MP-6-40-30-90	40	510	12
		MP-9-30-30-90	30	710	13
		MP-9-40-30-90	40	720	14

* Downlight fittings and anti-glare parts are sold separately.

