



Light Source

Bridgelux

MacAdam Ellipse

2-Step 3-Step

Material

Aluminum + PC Reflector

Degree of Protection

IP40

Color Temperature

2700K 3000K 4000K


CRI

97 90 80


Tilt Angle

35°

Module



Module	Article No.	LED	P(W)	CC(mA)	Voltage(V)	Angle(°)	CCT(K)	CRI	Flux(lm)
6.1W	M-6-40-27-80	V8	6.1	350	17.4	40	2700	80	670
	M-6-40-30-80	V8	6.1	350	17.4	40	3000	80	700
	M-6-40-27-90	V8	6.1	350	17.4	40	2700	90	560
8.9W	M-6-40-30-90	V8	6.1	350	17.4	40	3000	90	620
	M-9-40-27-80	Vero 10	8.9	350	25.3	40	2700	80	1030
	M-9-40-30-80	Vero 10	8.9	350	25.3	40	3000	80	1100
	M-9-40-27-90	Vero 10	8.9	350	25.3	40	2700	90	900
	M-9-40-30-90	Vero 10	8.9	350	25.3	40	3000	90	930



Anti-glare Part



Article No.	Finish	Installed LED Module	Angle(°)	Flux(lm)	UGR
SC-AG-MB	Matt Black	M-6-15-30-90	15	330	14
		M-6-28-30-90	20	310	12
		M-6-40-30-90	30	300	12
		M-6-60-30-90	40	300	13
		M-9-15-30-90	15	470	15
		M-9-28-30-90	20	460	15
		M-9-40-30-90	30	430	14
		M-9-60-30-90	40	440	15

* Downlight fittings and anti-glare parts are sold separately.

