



Light Source

Bridgelux

Degree of Protection

IP40

Material

Aluminum + PC

Color Temperature


2700K 3000K 4000K



CRI


97 90 80

MacAdam Ellipse

2-Step 3-Step



Module	Article No.	LED	P(W)	CC(mA)	Voltage(V)	Angle(°)	CCT(K)	CRI	Flux(lm)
	M-6-18L-30-90	V8	6.1	350	17.4	18	3000	90	630
	M-6-22L-30-90	V8	6.1	350	17.4	22	3000	90	630
	M-6-36L-30-90	V8	6.1	350	17.4	36	3000	90	620
	M-6-60L-30-90	V8	6.1	350	17.4	60	3000	90	610
	M-9-20L-30-90	Vero 10	8.9	350	25.3	20	3000	90	930
	M-9-24L-30-90	Vero 10	8.9	350	25.3	24	3000	90	930
	M-9-36L-30-90	Vero 10	8.9	350	25.3	36	3000	90	910
	M-9-60L-30-90	Vero 10	8.9	350	25.3	60	3000	90	900



Fitting Fixed Curve	Article No.	Diameter(mm)	Cut-out(mm)	Finish	Installed LED Module	Angle(°)	Flux(lm)	UGR
SC-95-FX-CV-MW	Ø95	Ø85	Matt White	M-6-18L-30-90	18	600	14	
				M-6-22L-30-90	22	590	14	
				M-6-36L-30-90	33	540	19	
				M-6-60L-30-90	50	510	21	
				M-9-20L-30-90	20	880	16	
				M-9-24L-30-90	24	870	16	
				M-9-36L-30-90	34	790	20	
				M-9-60L-30-90	50	750	23	
SC-95-FX-CV-MB	Ø95	Ø85	Matt Black	M-6-18L-30-90	18	570	8	
				M-6-22L-30-90	22	560	5	
				M-6-36L-30-90	32	470	9	
				M-6-60L-30-90	50	430	16	
				M-9-20L-30-90	20	830	8	
				M-9-24L-30-90	24	830	7	
				M-9-36L-30-90	34	710	10	
				M-9-60L-30-90	50	650	18	
SC-80-FX-CV-MW	Ø80	Ø70	Matt White	M-6-18L-30-90	18	580	16	
				M-6-22L-30-90	22	580	16	
				M-6-36L-30-90	32	520	19	
				M-6-60L-30-90	50	500	22	
				M-9-20L-30-90	20	860	16	
				M-9-24L-30-90	24	850	16	
				M-9-36L-30-90	33	770	21	
				M-9-60L-30-90	50	730	23	
SC-80-FX-CV-MB	Ø80	Ø70	Matt Black	M-6-18L-30-90	18	550	8	
				M-6-22L-30-90	22	540	5	
				M-6-36L-30-90	32	450	9	
				M-6-60L-30-90	50	410	15	
				M-9-20L-30-90	20	800	8	
				M-9-24L-30-90	24	800	5	
				M-9-36L-30-90	33	680	10	
				M-9-60L-30-90	50	620	17	

