



Light Source

Bridgelux

Degree of Protection

IP40

Material

Aluminum + PC

Color Temperature


2700K 3000K 4000K

CRI

97 90 80

MacAdam Ellipse

2-Step 3-Step



Module

Article No.

LED

P(W)

CC(mA)

Voltage(V)

Angle(°)


CCT(K)

CRI

Flux(lm)



M-6-18L-30-90	V8	6.1	350	17.4	18	3000	90	630
M-6-22L-30-90	V8	6.1	350	17.4	22	3000	90	630
M-6-36L-30-90	V8	6.1	350	17.4	36	3000	90	620
M-6-60L-30-90	V8	6.1	350	17.4	60	3000	90	610
M-9-20L-30-90	Vero 10	8.9	350	25.3	20	3000	90	930
M-9-24L-30-90	Vero 10	8.9	350	25.3	24	3000	90	930
M-9-36L-30-90	Vero 10	8.9	350	25.3	36	3000	90	910
M-9-60L-30-90	Vero 10	8.9	350	25.3	60	3000	90	900



Fitting Fixed	Article No.	Diameter(mm)	Cut-out(mm)	Finish	Installed LED Module	Angle(°)	Flux(lm)
	SC-95-FX-MW	Ø95	Ø80	Matt White	M-9-36L-30-90	36	910
	SC-95-FX-MB	Ø95	Ø80	Matt Black	M-9-36L-30-90	36	910
	SC-95-FX-CH	Ø95	Ø80	Chrome	M-9-36L-30-90	36	910
	SC-95-FX-AB	Ø95	Ø80	Aluminum Brushed	M-9-36L-30-90	36	910
	SC-95-FX-NB	Ø95	Ø80	Nickel Brushed	M-9-36L-30-90	36	910
	SC-80-FX-MW	Ø80	Ø70	Matt White	M-9-36L-30-90	36	910
	SC-80-FX-MB	Ø80	Ø70	Matt Black	M-9-36L-30-90	36	910
	SC-80-FX-CH	Ø80	Ø70	Chrome	M-9-36L-30-90	36	910
	SC-80-FX-AB	Ø80	Ø70	Aluminum Brushed	M-9-36L-30-90	36	910
	SC-80-FX-NB	Ø80	Ø70	Nickel Brushed	M-9-36L-30-90	36	910

