



Light Source

Bridgelux

MacAdam Ellipse

2-Step 3-Step

Material

Aluminum + PC Reflector

Degree of Protection

IP40

Color Temperature




2700K 3000K 4000K

CRI


97 90 80

Tilt Angle

25°



Module	Article No.	LED	P(W)	CC(mA)	Voltage(V)	Angle(°)	CCT(K)	CRI	Flux(lm)
	M-6-40-27-80	V8	6.1	350	17.4	40	2700	80	670
	M-6-40-30-80	V8	6.1	350	17.4	40	3000	80	700
	M-6-40-27-90	V8	6.1	350	17.4	40	2700	90	560
	M-6-40-30-90	V8	6.1	350	17.4	40	3000	90	620
	M-9-40-27-80	Vero 10	8.9	350	25.3	40	2700	80	1030
	M-9-40-30-80	Vero 10	8.9	350	25.3	40	3000	80	1100
	M-9-40-27-90	Vero 10	8.9	350	25.3	40	2700	90	900
	M-9-40-30-90	Vero 10	8.9	350	25.3	40	3000	90	930



Fitting Trimless	Article No.	Diameter(mm)	Cut-out(mm)	Tiltable(°)	Finish	Installed LED Module	Angle(°)	Flux(lm)
SC-TL-MW	Ø84	Ø90	25	Matt White	M-6-15-30-90	15	530	
					M-6-28-30-90	28	510	
					M-6-40-30-90	40	520	
					M-6-60-30-90	60	510	
					M-9-15-30-90	15	830	
					M-9-28-30-90	28	810	
					M-9-40-30-90	40	820	
					M-9-60-30-90	60	810	
SC-TL-DB	Ø84	Ø90	25	Deco Black	M-6-15-30-90	15	480	
					M-6-28-30-90	28	460	
					M-6-40-30-90	40	470	
					M-6-60-30-90	60	460	
					M-9-15-30-90	15	750	
					M-9-28-30-90	28	740	
					M-9-40-30-90	40	740	
					M-9-60-30-90	60	730	
SC-TL-DG	Ø84	Ø90	25	Deco Gold	M-6-15-30-90	15	480	
					M-6-28-30-90	28	460	
					M-6-40-30-90	40	470	
					M-6-60-30-90	60	460	
					M-9-15-30-90	15	750	
					M-9-28-30-90	28	740	
					M-9-40-30-90	40	740	
					M-9-60-30-90	60	730	

