



Fitting Material
Aluminium

Degree of Protection
IP20

Tilt
25°

Module Compatibility
Source Standard/Clip/HO

Control
DALI On/off Phase 0-10V

Finish
Matt white Matt black

Article No.	Control	Input Volt	Finish	Installed LED Module	P(W)	Angle(°)	CCT(K)	CRI	Flux(lm)
SM-6-DP-DA-MW	DALI	220-240V	matt white	M-6-40-30-90(6.1W)	7.9	40	3000	90	530
SM-DP-10-DA-MW	DALI	220-240V	matt white	M-9-40-30-90(8.9W)	11.4	40	3000	90	840
SM-20-DP-DA-MW	DALI	220-240V	matt white	M-15.5-42-30-90(15.5W)	19.4	42	3000	90	1540
SM-7-DP-OF-MW	On/off	220-240V	matt white	M-6-40-30-90(6.1W)	7.6	40	3000	90	530
SM-10-DP-OF-MW	On/off	220-240V	matt white	M-9-40-30-90(8.9W)	10.7	40	3000	90	840
SM-20-DP--OF-MW	On/off	220-240V	matt white	M-15.5-42-30-90(15.5W)	18.0	42	3000	90	1540
SM-7-DP-PD-MW	Phase	220-240V	matt white	M-6-40-30-90(6.1W)	8.1	40	3000	90	530
SM-10-DP-PD-MW	Phase	220-240V	matt white	M-9-40-30-90(8.9W)	11.1	40	3000	90	840
SM-20-DP-PD-MW	Phase	220-240V	matt white	M-15.5-42-30-90(15.5W)	18.0	42	3000	90	1540
SM-6-DP-VD-MW	0-10V	220-240V	matt white	M-6-40-30-90(6.1W)	8.4	40	3000	90	530
SM-10-DP-VD-MW	0-10V	220-240V	matt white	M-9-40-30-90(8.9W)	11.9	40	3000	90	840
SM-20-DP-VD-MW	0-10V	220-240V	matt white	M-15.5-42-30-90(15.5W)	19.4	42	3000	90	1540

