



Light Source

Bridgelux

Rotate Angle

359°

Material

Aluminum + PC Reflector

MacAdam Ellipse

2-Step 3-Step

Color Temperature

2700K 3000K 4000K

Degree of Protection

IP40


CRI

97 90 80


Tilt Angle

25°

Module



Module	Article No.	LED	P(W)	CC(mA)	Voltage(V)	Angle(°)	CCT(K)	CRI	Flux(lm)
	M-6-40-27-80	V8	6.1	350	17.4	40	2700	80	670
	M-6-40-30-80	V8	6.1	350	17.4	40	3000	80	700
	M-6-40-27-90	V8	6.1	350	17.4	40	2700	90	560
	M-6-40-30-90	V8	6.1	350	17.4	40	3000	90	620
	M-9-40-27-80	Vero 10	8.9	350	25.3	40	2700	80	1030
	M-9-40-30-80	Vero 10	8.9	350	25.3	40	3000	80	1100
	M-9-40-27-90	Vero 10	8.9	350	25.3	40	2700	90	900
	M-9-40-30-90	Vero 10	8.9	350	25.3	40	3000	90	930



Fitting Spin

Article No.	Diameter(mm)	Cut-out(mm)	Tilttable(°)	Finish	Installed LED Module	Angle(°)	Flux(lm)
SS-110-MW	Ø110	Ø98	25	Mat White	M-9-40-30-90	40	930
SS-110-MB	Ø110	Ø98	25	Mat Black	M-9-40-30-90	40	930

